

CLAIMS

1. A method of granting, to a user communications device,  
access to a service provided by a plurality of service  
communications devices, the method comprising the steps  
of

initiating a first communications link between the user  
communications device and a first one of the plurality of  
service communications devices;

generating an access key code;

10 storing a first data item in a first storage means of the  
user communications device, the first data item  
indicating the access key code;

15 characterised in that the access key code  
is indicative of the user communications device and the  
service; and the method further comprises the steps of

making the access key code available to at least a second  
one of the plurality of service communications devices  
via a communications network;

20 initiating a second communications link between the user  
communications device and the second service  
communications device; and

using the access key code to mutually authenticate the  
user communications device and the second service  
communications device.

25 2. A method according to claim 1, characterised  
in that

the user communications device and the plurality of service communications devices each comprise a Bluetooth communications unit;

the first and second communications links are Bluetooth communications links;

the access key code is a baseband link key; and

the step of generating an access key code is part of a Bluetooth pairing procedure.

3. A method according to claim 1,  
10 c h a r a c t e r i s e d i n that the user communications device is a mobile radio terminal.

4. A method according to claim 1,  
c h a r a c t e r i s e d i n that the first service communications device is a designated  
15 subscription communications device.

5. A method according to claim 1,  
c h a r a c t e r i s e d i n that the method further comprises the steps of

transmitting a service identification code from the first  
20 service communications device to the user communications device via the first communications link;

storing a second data item in the first storage means in relation to the access key code, the second data item indicating the service identification code; and

25 the step of using the access key code to mutually authenticate the user communications device and the second service communications device further comprises the steps of

1005580-120701

transmitting the service identification code from the second service communications device to the user communications device via the second communications link; and

- 5 retrieving, based on the service identification code, the access key code from the first storage means.

6. A method according to claim 1,  
c h a r a c t e r i s e d i n that the method  
further comprises the step of using the access key code  
10 to generate an encryption key for encrypting the second communications link.

7. A method according to claim 1,  
c h a r a c t e r i s e d i n that the step of  
generating an access key code comprises the steps of  
15 generating a first part of the access key code in the user communications device; generating a second part of the access key code in the first service communications device; transmitting the first part of the access key code from the user communications device to the first  
20 service communications device; and transmitting the second part of the access key code from the first service communications device to the user communications device.

8. A method according to claim 1,  
c h a r a c t e r i s e d i n that the step of  
25 making the access key code available to at least a second one of the plurality of service communications devices via a communications network comprises the steps of

transmitting the access key code to the second service communications device; and

1000000.120701

storing a third data item in a second storage means of the second service communications device, the third data item indicating the access key code.

9. A method according to claim 1,

- 5 c h a r a c t e r i s e d i n that the step of making the access key code available to at least a second one of the plurality of service communications devices via a communications network comprises the step of storing a fourth data item in a database, the fourth data  
10 item indicating the access key code; and

the step of using the access key code to mutually authenticate the user communications device and the second service communications device comprises the steps of

- 15 retrieving the access key code from the database; and transmitting the retrieved access key code via the communications network to the second service communications device.

- 20 10. A communications system comprising a user communications device, a first and a second service communications device, the first and second service communications devices each providing a service;

- the user communications device and the first and second service communications devices each including a  
25 respective transmit/receive unit for transmitting and receiving data signals via respective communications links between the user communications device and a selected one of the first and second service communications devices;

- 30 a selected one of the user communications device and the first service communications device comprising first

1005000-12704

processing means adapted to generate at least a part of an access key code during an initialisation procedure of a first communications link between the user communications device and the first service communications device, the access key code being indicative of the user communications device and the service;

the user communications device including first storage means adapted to store a first data item indicating the access key code; and

second processing means adapted to retrieve the access key code from the first storage means and to use the retrieved access key code during an authentication procedure of a second communications link between the user communications device and the second service communications device;

the system including a communications network interconnecting the first and second service communications devices and adapted to make the access key code available to at least the second service communications device;

the second service communications device including third processing means adapted to receive the access key code via the communications network and to use the received access key code during the authentication procedure of the second communications link.

11. A communications system according to claim 10, characterised in that

the transmit/receive units of the user communications device and the first and second service communications devices each comprise a Bluetooth communications unit;

1005000-120701

the first and second communications links are Bluetooth communications links;

the access key code is a baseband link key; and

the initialisation procedure is a Bluetooth pairing  
5 procedure.

12. A communications system according to  
claim 10, characterised in  
that the user communications device is a mobile radio  
terminal.

10 13. A communications system according to  
claim 10, characterised in  
that the first service communications device is a  
designated subscription communications device.

15 14. A communications system according to  
claim 10, characterised in  
that

the first service communications device is adapted to  
transmit a service identification code to the user  
communications device via the first communications link;

20 the first storage means is adapted to store, in relation  
to the access key code, a second data item indicating the  
service identification code;

the second service communications device is adapted to  
transmit the service identification code to the user  
25 communications device via the second communications link  
during the authentication procedure; and

the second processing means is adapted to retrieve, based  
on the service identification code, the access key code  
from the first storage means.

1005000-120701

15. A communications system according to claim 10, characterised in that a selected one of the second and third processing means is adapted to generate an encryption key for encrypting the second communications link on the basis of the access key code.
16. A communications system according to claim 10, characterised in that the second service communications device further comprises second storage means adapted to store a third data item indicating the access key code.
17. A communications system according to claim 10, characterised in that the system further comprises a third storage means connected to the communications network and adapted to store a fourth data item indicating the access key code; and the third processing means is adapted to retrieve the access key code from the third storage means via the communications network.
18. A user communications device comprising a first transmit/receive unit for transmitting data signals to and receiving data signals from selected ones of a plurality of service communications devices providing a service;
- first storage means adapted to store a first data item indicating an access key code generated during an initialisation procedure of a first communications link between the user communications device and a first one of the plurality of service communications devices, the access key code being indicative of the user communications device and the service;

10005200-120701

first processing means adapted to retrieve the access key code from the first storage means and to use the retrieved access key code during an authentication procedure of a second communications link between the user communications device and a second one of the plurality of service communications devices.

19. A user communications device according to claim 18, characterised in that

the first transmit/receive unit comprises a Bluetooth communications unit;

the first and second communications links are Bluetooth communications links;

the access key code is a baseband link key; and

the initialisation procedure is a Bluetooth pairing procedure.

20. A user communications device according to claim 18, characterised in that the user communications device is a mobile radio terminal.

21. A user communications device according to claim 18, characterised in that

the first transmit/receive unit is adapted to receive a service identification code from the first service communications device via the first communications link;

the first storage means is adapted to store, in relation to the access key code, a second data item indicating the service identification code; and



the first transmit/receive unit is further adapted to receive, during the authentication procedure, the service identification code from the second service communications device via the second communications link;  
5 and

the first processing means is adapted to retrieve, based on the service identification code, the access key code from the first storage means.

10 22. A user communications device according to claim 18, characterised in that the first processing means is adapted to generate an encryption key for encrypting the second communications link on the basis of the access key code.

15 23. A user communications device according to claim 18, characterised in that the user communications device further comprises second processing means adapted to generate at least a part of the access key code.

20 24. A communications system comprising a first and a second service communications device each providing a service;

the first service communications device including

a first transmit/receive unit for transmitting data signals to and receiving data signals from a user  
25 communications device via a first communications link;

first processing means adapted to perform an initialisation procedure of the first communications link, the initialisation procedure including the generation of an access key code indicative of the user  
30 communications device and the service;

1000000-120701

the system including a communications network interconnecting the first and second service communications devices and adapted to make the access key code available to at least the second service

5 communications device;

the second service communications device including

a second transmit/receive unit for transmitting data signals to and receiving data signals from the user communications device via a second communications link;

10 second processing means adapted to receive the access key code via the communications network and to use the received access key code during an authentication procedure of the second communications link.

25. A communications system according to claim 24,

15 c h a r a c t e r i s e d i n that the first processing means is adapted to generate at least a part of the access key code.

1005080-120701